

# Flammable Storage Cabinet Specification Sheet

## SMS-01-V43



Fusible link provided with self closing models - Melts to activate self close at 165°

Self closing mechanism is separate from storage area. Doors indexed to close and latch



16 Gauge double walled steel construction with 1-1/2" of space between the walls

Wire welded construction thought out the cabinet

Durable safety yellow, high gloss, polyurethane powder coat paint

High Quality lockable Flush mount handle



3 Point lockable Latching System

Electrical ground in side of cabinet

Leveling feet visible under cabinet

2" deep leak proof sump

2" wide louvered panels support shelves.

Shelves adjust on 4" centers

MIG welded continuous hinges

Bunged air vents with flame arrestors on each side of the cabinet

- All Flammable Cabinets are FM approved
- 90 Years of manufacturing safety equipment
- High quality self closing mechanism
- Improved security with recessed locking mechanism
- 10 year limited warranty





## FM Approved Flammable Safety Cabinet

- Sturdy all welded 16 gauge double wall steel construction
- Choice of manual or self closing doors
- 2" wide louvers support shelves, adjustable on 4" centers
- 2" Deep leak proof base
- Safely contains hazardous chemicals reducing the risk of fire
- Units come fully assembled and ready for use
- Electrical ground on bottom right hand side to aid in the elimination of an electrostatic discharge
- Improved security with recessed lockable paddle latch and 3 point locking system
- Bunged air vents on each side of the cabinet allows for ventilation
- Safety yellow powder coat finish

Model	Gallon capacity (L)	Overall Dim: WxDxH (In)	Shelves	Optional Shelf Part	Door Style	Ship Wt. (Lbs.)
1004M-50	4 (15)	17-3/8 x 18-1/8 x 22-1/8 (442 x 461 x 562)	1		Manual	104
1004S-50	4 (15)	17-3/8 x 18-1/8 x 23-3/8 (442 x 461 x 593)	1		Self Closing	110
1012MH-50	12 (45) - Horizontal	43 1/8" x 18 1/8" x 18 1/8" (1095 x 461 x 461)	1	FS-SH-1439	Manual	165
1012M-50	12 (45)	23" x 18" x 35" (584 x 457 x 889)	1	FS-SH-1419	Manual	159
1012S-50	12 (45)	23" x 18" x 36-3/8" (584 x 457 x 924)	1	FS-SH-1419	Self Closing	167
1016M-50	16 (61)	23 x 18 x 44 (584 x 457 x 1118)	1	FS-SH-1419	Manual	186
1016S-50	16 (61)	23 x 18 x 45 3/8 (584 x 457 x 1153)	1	FS-SH-1419	Self Closing	194
1022M-50	22 (83)	23-5/16 x 18-1/8 x 65 (592 x 461 x 1651)	2	FS-SH-1419	Manual	283
1022S-50	22 (83)	23-5/16 x 18-1/8 x 66-3/8 (592 x 461 x 1686)	2	FS-SH-1419	Self Closing	296
1030M-50	30 (114)	43" x 18" x 44" (1092 x 457 x 1118)	1	FS-SH-1439	Manual	285
1030S-50	30 (114)	43" x 18" x 45-3/8" (1092 x 457 x 1153)	1	FS-SH-1439	Self Closing	309
1045M-50	45 (170)	43" x 18" x 65" (1092 x 457 x 1651)	2	FS-SH-1439	Manual	409
1045S-50	45 (170)	43" x 18" x 66-3/8" (1092 x 457 x 1686)	2	FS-SH-1439	Self Closing	423
1060M-50	60 (227)	34" x 34" x 65" (834 x 864 x 1651)	2	FS-SH-2930	Manual	509
1060S-50	60 (227)	34" x 34" x 66-3/8" (834 x 864 x 1686)	2	FS-SH-2930	Self Closing	533
1090M-50	90 (340)	43" x 34" x 65" (1092 x 864 x 1651)	2	FS-SH-2939	Manual	587
1090S-50	90 (340)	43" x 34" x 66-3/8" (1092 x 864 x 1686)	2	FS-SH-2939	Self Closing	623

FOB TX

