

WdEYWfWcEYWWcEYUUDYWWdE? FFI,F



SRE4003M

WHEN ORDERING, MODEL NUMBERS MUST BE COMPLETED AS FOLLOWS

H for posts with a smooth surface
R for posts with a perforated surface

BOLTED uprights D
WELEDDED uprights E

SH SR

S ↓ 4001M

e.g., SHD4001
For a mobile shelving unit with smooth surface posts and bolted uprights.

- The preconfigured models in this section include a mobile base for Spider® Shelving and four 4" casters, including two swivel casters with total-lock brakes and two rigid casters
- To calculate the actual width of the base, add 3³/₁₆" to the nominal width
- To calculate the actual depth of the base, add 3/4" to the nominal depth
- The preconfigured models in this section include open shelving uprights, braces and BOX shelves
- Load capacity: 1,000lb. per base
- All preconfigured models are quick and easy to assemble and can be disassembled when not in use

W	DIMENSIONS			NUMBER OF SHELVES
	D	H	ACTUAL H	6
36"	18"	63"	68 1/4"	S_ _4001M
	24"	63"	68 1/4"	S_ _4002M
		75"	80 1/4"	S_ _4003M
42"	18"	63"	68 1/4"	S_ _4004M
	24"	63"	68 1/4"	S_ _4005M
		75"	80 1/4"	S_ _4006M
48"	18"	63"	68 1/4"	S_ _4007M
	24"	63"	68 1/4"	S_ _4008M
		75"	80 1/4"	S_ _4009M

NOTES: For a side-to-side double shelving unit, see SH99 Mobile Base for Mini-Racking, see page 129.
Not compatible with drawers or roll-out shelves in shelving and SH41, SH43, SH91 and SH93 doors.



SRD9002 M



SRE4010 M

