

**DESIGNED  
FOR  
COMMERCIAL  
CULTIVATION.  
ENGINEERED FOR  
RESULTS.**

# TURN AISLES INTO CANOPY.

**UP TO  
90%  
CANOPY COVERAGE**

**UP TO  
35 LBS/FT<sup>2</sup>  
TRAY LOADING CAPACITY**

**5 BENCH TYPES  
ONE SYSTEM. EVERY GROW.**

**GALVANIZED STEEL  
FRAME**  
1" tubing — built tough for  
long-term reliability

**PLANT SUPPORT SYSTEM**  
Optional add-on — available  
on every bench type

**FULL INSTALLATION SUPPORT**  
CAD drawings, anchors, and  
delivery quotes available

**ADJUSTABLE HEIGHT**  
9" to 38" floor-to-surface  
depending on bench type

**MADE TO ORDER**  
No stock SKU — every bench  
custom-built in Sycamore, IL


**DESIGN SERVICES  
AVAILABLE**  
Layout and space analysis  
provided at no charge

**EBB & FLOW OR  
EXPANDED METAL**  
Interchangeable top options  
across all bench types

**OVERBUILT ON PURPOSE**  
Every bench engineered for  
heavy loads and daily use


**PROUDLY MADE  
IN AMERICA**

## STATIONARY BENCH




**8 WIDTHS**  
2'-6"6"

## STANDARD ROLL BENCH




**6 WIDTHS**  
4'-6"6"

## MAX ROLL BENCH



**7 WIDTHS**  
3'-6"6"

## TRACK BENCH W/ MECH. ASSIST



**7 WIDTHS**  
2'-6"6"

## TRACK BENCH W/O MECH. ASSIST



**7 WIDTHS**  
2'-6"6"

**LET'S BUILD A BETTER  
GROW ENVIRONMENT.**

contact us today to build  
your perfect grow space.

1-866-285-8646

sales@storemorestore.com

storemorestore.com

2535 E. State Hwy. 121  
Lewisville, TX 75056

# ONE SYSTEM. EVERY GROW.



A Division of SouthWest Solutions Group

1-866-285-8646 | sales@storemorestore.com | storemorestore.com

## BENCH TYPE COMPARISON

BENCH TYPE	BEST FOR	ROLLING	FLOOR ANCHORED	MECHANICAL ASSIST OPTIONAL	LENGTHS
<b>Stationary</b>	Greenhouses, research, retail displays	✗	Optional	✗	Up to 120'
<b>Standard Roll</b>	Single-direction rolling	✓	✓	✓	Up to 120'
<b>Max Roll</b>	Extended travel, high canopy travel	✓	✓	✓	Up to 120'
<b>Track (Mech)</b>	Chain-driven mechanical assist	✓	✓	✓	Up to 60'
<b>Track (Manual)</b>	Manual positioning, simple install	✓	✓	✗	Up to 30'

## FULL PRODUCT SPECIFICATIONS


BENCH TYPE	AVAILABLE WIDTHS	HEIGHT	LENGTH	NOTES
<b>Stationary</b>	2', 3', 4', 4'6", 5', 5'6", 6', 6'6"	9"-36"	4'-120' (1" incr.)	No floor anchoring req.
<b>Standard Roll</b>	4', 4'6", 5', 5'6", 6', 6'6"	9"-36"	4'-120' (1" incr.)	Concrete floor anchoring req.
<b>Max Roll</b>	3', 4', 4'6", 5', 5'6", 6', 6'6"	9"-36"	4'-120' (1" incr.)	Concrete floor anchoring req.
<b>Track (Mech)</b>	3', 4', 4'6", 5', 5'6", 6', 6'6"	14"-38"	8'-60' (1" incr.)	Drive handle for mobility
<b>Track (Manual)</b>	3', 4', 4'6", 5', 5'6", 6', 6'6"	12"-38"	8'-30' (1" incr.)	Anchored rail

## MAX ROLL TRAVEL DISTANCE

BENCH WIDTH	STANDARD ROLL	MAX ROLL
3'	—	5.75'
4'	7.5'	9.75'
4'6"	8.75'	11.75'
5'	9.75'	13.25'
5'6"	10.5'	15'
6'	11.5'	15.5'
6'6"	10.75'	16.5'


### EBB & FLOW TRAY RETROFIT

- Upgrade existing benches to sub-irrigation
- Crossbars: 50cm and / 33cm to D-I / 25cm extra-heavy
- Must support ~4 lbs/sq ft under irrigation
- Must be fully levelable — critical for E&F trays
- Plumbing access required at tray end



### PLANT SUPPORT SYSTEM

- Available on all bench types
- Uprights attach to side rails; adjustable crossbar height



# MAXIMIZE EVERY FOOT. MAXIMIZE EVERY HARVEST.

CONTACT SSG TODAY TO DESIGN YOUR SYSTEM.



**BETTER  
AIRFLOW**



**STRONGER  
YIELDS**



**MAXIMIZED  
SPACE**



**EASIER  
WORKFLOW**



**BUILT TO  
LAST**