

<b>Kardex Megamat 120 VCM</b>									
<b>Equipment Specifications:</b>									
<b>Overall Unit Specifications:</b>									
Base unit includes lockable bi-parting door, dust cover/top, safety circuits, safety light curtain, emergency stops, touch bars, motor, manual handcrank, electronics and TUV label.									
<p style="text-align: center;">Quantity of Carousels : 1                  Model Number : 120-2015W                  Overall Unit Width : 116.02 inches (2947 mm)                  Overall Unit Depth without posting board : 45.47 inches (1155 mm)                  Work Counter Posting Board Depth : 11.82 inches (300 mm)                  Overall Unit Height : 175.20 inches (4450 mm)                  Unit Weight Empty : 4664 lbs.                  Unit Weight - Fully Loaded : 10384 lbs.                  Maximum Load : 5720 lbs. total stored capacity                  Top Tolerance at Balanced Load : +/- 15mm (.059 inch)                  Maximum Imbalance Load : 660 lbs.                  Cycle Speed : 7.0 inches / second                  Average Access Time : 10.7 seconds                  Color Selection (Endframes) : Standard-Light Gray                  Color Selection (Panels) : Standard - Silver Fir Blue                  Noise Level : Less than 60 db(A)</p>									
<b>Access Opening Information:</b>									
<p style="text-align: center;">Work Counter Type and Height : Standing 39.4 in. (1000mm)                  Work Counter Finish : Standard Light Gray Finish                  Door Type : Standard Manual Bi-parting Door w/Keylock                  Opening Clear Height : 19.41 in. (493mm)                  Access Lighting : Full Width Light Above Access Opening</p>									
<b>Power and Controls:</b>									
<p style="text-align: center;">Power Supply : 110 Volt /1-/60 Hz                  Drive, Gear Motor : AC - Gear Motor - 1.5 kva                  AMP Draw : 16 AMP                  Average Power Consumption : 1.2 KVA (3.0 KVA Maximum)                  Control : T0 Control                  Controller Location : Work Counter/Table                  E-Stop : Included Left and Right Side of Access Opening                  Computer Interface : No                  Imbalance Detection : Imbalance Detection Module Included</p> <p style="text-align: right;">Breaker Size : 20*                  *Cannot be wired to a breaker or outlet that uses a GFI circuit.</p>									
<b>Standard Safety Features</b>									
Expanded Error Indicator					Upper and Lower Mechanical Safety Bars (Doors)				
Safety Light Curtain					Safety Switches for Lower Front Access Panel and Hand Crank Opening				
E-Stop Left and Right Side					Emergency Service Switch				
<b>Standard Features included in Base unit</b>									
<b>Electronics Located in the Bottom Access Panel</b>					<b>Top Dust Cover</b>				
<b>Hand Crank for Installation of Carriers and Service</b>					<b>Access for Service from Front</b>				
<b>Additional Features and Options</b>									
<b>Dirak Access Panel Lock Kit Included</b>									
<b>Carrier Specifications:</b>									
<b>Specifications Per Carrier</b>									
Carousel Carrier Configuration	:	Qty	Clear Height	Clear Width	Clear Depth	Max. Capacity	Avg. Capacity	LFI Per Carrier	Total LFI Per Carrier Style
Multipurpose Carrier with Additional Shelves	:	120	6.65	101.38	16.1	143 lbs.	143 lbs.	101	2020
Additional shelf level	:	40	6.65	101.38	16.1	143 lbs.	143 lbs.	50	2020
<b>Total Linear Filing Inches (LFI) for 1 unit(s)</b>			<b>2020</b>						
<i>Multimedia Carriers/Drawers are not included in Total LFI calculation</i>									
<i>*Avg. capacity is based on a unit configured with one carrier type.</i>									