

<b>Kardex Megamat 125 VCM</b>									
<b>Equipment Specifications:</b>									
<b>Overall Unit Specifications:</b>									
Base unit includes lockable bi-parting door, dust cover/top, safety circuits, safety light curtain, emergency stops, touch bars, motor, manual handcrank, electronics and TUV label.									
<p style="text-align: center;">           Quantity of Carousels : 1            Model Number : 125-1111X            Overall Unit Width : 128.70 inches (3269 mm)            Overall Unit Depth without posting board : 47.32 inches (1202 mm)            Work Counter Posting Board Depth : 11.82 inches (300 mm)            Overall Unit Height : 79.73 inches (2025 mm)            Unit Weight Empty : 2456 lbs.            Unit Weight - Fully Loaded : 5151 lbs.            Maximum Load : 2695 lbs. total stored capacity            Top Tolerance at Balanced Load : +/- 15mm (.059 inch)            Maximum Imbalance Load : 660 lbs.            Cycle Speed : 7.0 inches / second            Average Access Time : 4.3 seconds            Color Selection (Endframes) : Standard-Light Gray            Color Selection (Panels) : Standard - Silver Fir Blue            Noise Level : Less than 60 db(A)         </p>									
<b>Access Opening Information:</b>									
<p style="text-align: center;">           Work Counter Type and Height : Standing 39.4 in. (1000mm)            Work Counter Finish : Standard Light Gray Finish            Door Type : Standard Manual Bi-parting Door w/Keylock            Opening Clear Height : 19.41 in. (493mm)            Access Lighting : Full Width Light Above Access Opening         </p>									
<b>Power and Controls:</b>									
<p style="text-align: center;">           Power Supply : 110 Volt /1-/60 Hz            Drive, Gear Motor : AC - Gear Motor - 1.5 kva            AMP Draw : 16 AMP            Average Power Consumption : 1.2 KVA (3.0 KVA Maximum)            Control : T0 Control            Controller Location : Work Counter/Table            E-Stop : Included Left and Right Side of Access Opening            Computer Interface : No            Imbalance Detection : Imbalance Detection Module Included         </p> <p style="text-align: right;">Breaker Size : 20* *Cannot be wired to a breaker or outlet that uses a GFI circuit.</p>									
<b>Standard Safety Features</b>									
Expanded Error Indicator					Upper and Lower Mechanical Safety Bars (Doors)				
Safety Light Curtain					Safety Switches for Lower Front Access Panel and Hand Crank Opening				
E-Stop Left and Right Side					Emergency Service Switch				
<b>Standard Features included in Base unit</b>									
<b>Electronics Located in the Bottom Access Panel</b>					<b>Top Dust Cover</b>				
<b>Hand Crank for Installation of Carriers and Service</b>					<b>Access for Service from Front</b>				
<b>Additional Features and Options</b>									
<b>Dirak Access Panel Lock Kit Included</b>									
<b>Carrier Specifications:</b>									
<b>Specifications Per Carrier</b>									
<b>Carousel Carrier Configuration</b>	<b>:</b>	<b>Qty</b>	<b>Clear Height</b>	<b>Clear Width</b>	<b>Clear Depth</b>	<b>Max. Capacity</b>	<b>Avg. Capacity</b>	<b>LFI Per Carrier</b>	<b>Total LFI Per Carrier Style</b>
Carrier with 60 Degree Lip	:	11	9.88	114.53	15.19	245 lbs.	245 lbs.	114	1254
<b>Total Linear Filing Inches (LFI) for 1 unit(s)</b>			<b>1254</b>	<i>Multimedia Carriers/Drawers are not included in Total LFI calculation</i>					
<i>*Avg. capacity is based on a unit configured with one carrier type.</i>									