

PRODUCT SPECIFICATIONS

MODEL

PM5-10W

DESCRIPTION

PM 10 DRAWER CABINET WITH 5" DRAWERS – BULK FILING

DIMENSIONS

56" high x 36" wide x 24" deep

WEIGHT

Approximately: 420 lbs. est. shipping weight
400 lbs. est. empty weight
1,000 lbs. est. loaded weight

CAPACITY

22-1/4" Linear filing inches per row in drawer
6 Rows per drawer
10 Drawers per cabinet
1,335 Filing inches per cabinet
120 LTO IN CASE per drawers
1,200 LTO IN CASE per cabinet

CONSTRUCTION

Steel gauges used are as follows:

Cabinets:

- End panel: 20 gauge
- Back panel: 20 gauge
- Bottom: 18 gauge
- Vertical structural members: 16 gauge
- Horizontal structural members: 16 gauge

Drawers:

- Drawer Front: 20 gauge
- Drawer Front Pull: 14 gauge
- Drawer Sides: 20 gauge
- Drawer Body: 20 gauge
- Drawer Dividers: 22 gauge



Sheet metal used is ASTM A-366, Class 1, carbon sheet steel, matte finish. All corners are welded and ground smooth and cabinet is free of any raw edges.

Fully Welded Cabinet

Heavy-duty all-welded construction to assure years of lasting service. Internal structure consists of an all-welded frame at front made of internal structural vertical and horizontal hat sections. Four corners of top are formed closed, and sanded to form a smooth, seamless corner. End panels and back panels are formed, and spot welded to mating parts.

Fully Welded Drawers

Drawer bodies are spot welded and free of burrs or sharp edges. Each drawer has 6 rows of front to back filing. Welded dividers separate each row. Row dimensions: 4-3/8" H x 4-11/16" W x 22-1/4" D
Maximum form size: 4-5/16" H x 4-1/2" W x 1-1/16"

(Continued)

DRAWERS

Full width drawer pulls with label holders on both ends.
Suspensions are Accuride 3600 Series ball bearing 3-member, full extension, furniture quality slides with a heavy-duty load rating

Hold-in detent provides to prevent drawers from “drifting” open.

Precision ball bearing slides are provided to support the load and maintain years of smooth operation. Slides are electro-zinc plated to prevent corrosion

Safety feature: The cabinet is equipped with a fully interlocking drawers, allowing only one drawer to be opened at a time, preventing accidental tipping.

ROW COMPRESSOR

Each cabinet comes with one “4x4 Bookend” to compress the media in the drawer row. Additional Bookends can be ordered as needed

LOCK

Cabinet drawer lock is optional. Accommodations are included on every cabinet so that locks can be added in the field if required. The flush mounted key lock is located on the center of the cabinet top.

LEVELING GLIDES

Provided at each corner of the cabinet, easily accessible from inside of the cabinet.

PAINTING

All parts pass through an automatic conveyerized washer system. All interior and exterior surfaces are thoroughly cleaned and sealed with a rust inhibitive iron phosphate coating prior to a baked powder coat finish.

Finish is powder coat and shall have a minimum 1.0 mil dry film thickness that is level, smooth, even and non-abrasive, without runs, wrinkles, grittiness or roughness.

Finish complies with U. S. National Archives specifications.

CARTONING

Cabinets have corrugated top and bottom caps and internal pads with full height corner protectors that are banded and stretch wrapped with plastic film.

10-YEAR WARRANTY

This product has a 10-year limited warranty to be free from defects in workmanship and material for a full 10 years.