

# Forklift Dumping Hopper - SMS-09-V46-H



FULL 90°  
DUMP ANGLE

## Low Profile 90° Self-Dumping Steel Hoppers

Units feature a full 90° dump angle with a cushioned rubber bumper stop. The low profile design is essential for convenient loading. Dumping with a fork truck is quick and simple. A cable is pulled from the seat of the fork truck to dump the hopper. The unit returns to an upright and locked position when lowered to the ground. A safety restraint is provided to secure the hopper to the fork truck. 22" L usable fork pockets measure 7" W x 2" H. Formed base thickness is ¼". Blue baked-in powder-coated toughness with galvanized base. Models H-25 and H-50 may be stacked together, as well as, the H-100 and the H-150 models. Never stack hoppers more than 3 high.



48 Hours  
to Ship

CA Residents see  
WARNING A, Pg. 459

Height from the Front Lip to the Floor on "H" series Hoppers	
H-25.....	14 <sup>9</sup> / <sub>16</sub> "
H-50.....	20 <sup>5</sup> / <sub>8</sub> "
H-100.....	20 <sup>5</sup> / <sub>8</sub> "
H-150.....	26 <sup>15</sup> / <sub>16</sub> "

MODEL NUMBER	VOLUME CUBIC YARDS	UNIFORM CAPACITY	OVERALL SIZE (W x L x H)	FORK POCKET CENTERS	WEIGHT (POUND)
<b>LIGHT DUTY • 12 GAUGE STEEL</b>					
SMS-09-V46-H-25-LD	1/4	2,000 lb.	27" x 46 <sup>1</sup> / <sub>8</sub> " x 21 <sup>3</sup> / <sub>8</sub> "	11 <sup>5</sup> / <sub>8</sub> "	179
SMS-09-V46-H-50-LD	1/2	2,000 lb.	27" x 51 <sup>3</sup> / <sub>16</sub> " x 28 <sup>1</sup> / <sub>8</sub> "	11 <sup>5</sup> / <sub>8</sub> "	210
SMS-09-V46-H-100-LD	1	2,000 lb.	51" x 51 <sup>3</sup> / <sub>16</sub> " x 28 <sup>1</sup> / <sub>8</sub> "	21 <sup>5</sup> / <sub>8</sub> "	311
SMS-09-V46-H-150-LD	1½	2,000 lb.	51" x 56 <sup>1</sup> / <sub>2</sub> " x 38 <sup>5</sup> / <sub>8</sub> "	21 <sup>5</sup> / <sub>8</sub> "	360
<b>MEDIUM DUTY • 10 GAUGE STEEL</b>					
SMS-09-V46-H-25-MD	1/4	4,000 lb.	27" x 46 <sup>1</sup> / <sub>8</sub> " x 21 <sup>3</sup> / <sub>8</sub> "	11 <sup>5</sup> / <sub>8</sub> "	207
SMS-09-V46-H-50-MD	1/2	4,000 lb.	27" x 51 <sup>3</sup> / <sub>16</sub> " x 28 <sup>3</sup> / <sub>16</sub> "	11 <sup>5</sup> / <sub>8</sub> "	243
SMS-09-V46-H-100-MD	1	4,000 lb.	51" x 51 <sup>3</sup> / <sub>16</sub> " x 28 <sup>1</sup> / <sub>8</sub> "	21 <sup>5</sup> / <sub>8</sub> "	362
SMS-09-V46-H-150-MD	1½	4,000 lb.	51" x 56 <sup>9</sup> / <sub>16</sub> " x 38 <sup>5</sup> / <sub>8</sub> "	21 <sup>5</sup> / <sub>8</sub> "	435
<b>HEAVY DUTY • 8 GAUGE STEEL</b>					
SMS-09-V46-H-25-HD	1/4	6,000 lb.	27" x 46 <sup>3</sup> / <sub>16</sub> " x 21 <sup>3</sup> / <sub>8</sub> "	11 <sup>5</sup> / <sub>8</sub> "	207
SMS-09-V46-H-50-HD	½	6,000 lb.	27" x 51 <sup>1</sup> / <sub>4</sub> " x 28 <sup>3</sup> / <sub>16</sub> "	11 <sup>5</sup> / <sub>8</sub> "	262
SMS-09-V46-H-100-HD	1	6,000 lb.	51" x 51 <sup>1</sup> / <sub>4</sub> " x 28 <sup>3</sup> / <sub>16</sub> "	21 <sup>5</sup> / <sub>8</sub> "	398
SMS-09-V46-H-150-HD	1½	6,000 lb.	51" x 56 <sup>9</sup> / <sub>16</sub> " x 38 <sup>11</sup> / <sub>16</sub> "	21 <sup>5</sup> / <sub>8</sub> "	472

